

MEMBRÁNOVÁ DMYCHADLA



DB40, DB60 DBMX80, 100, 120 DBMX150, 200

- dlouhá životnost ✓
- tuhá konstrukce ✓
- minimální údržba ✓
- minimální spotřeba ✓

Technické parametry membránových kompresorů



Typ	DB40	DB60	DBMX80	DBMX100	DBMX120	DBMX150	DBMX200	DBMX250	DBMX300	
Provozní tlak (mbar)	Průtok vzduchu (l/min) [spotřeba Watt]									
0	70 [45]	102 [73]	143 [108]	152 [124]	175 [151]	255 [171]	276 [233]	462 [295]	489 [387]	
50	63 [45]	93 [71]	128 [105]	140 [122]	161 [148]	243 [168]	256 [221]	409 [284]	443 [379]	
100	54 [43]	80 [67]	113 [99]	128 [116]	147 [141]	217 [158]	236 [212]	356 [262]	397 [357]	
150	44 [40]	68 [63]	98 [91]	116 [109]	133 [132]	183 [145]	216 [201]	303 [233]	351 [329]	
200	34 [36]	57 [57]	83 [82]	100 [100]	120 [122]	150 [130]	200 [186]	250 [202]	300 [298]	
250	24 [31]	44 [52]	68 [71]	84 [90]	103 [111]	115 [112]	163 [169]	185 [167]	244 [262]	
Optimální provozní tlak	< 250 mbar									

Napětí	230 V / 50 Hz								
Max. el. proud (A)	0,41	0,59	0,63	0,82	0,94	1,2	1,75	1,8	2,6
Hlučnost - 1,5 m (dB)	48	48	45	45	46	48	48	55	56
Hmotnost (kg)	6,0	6,8	8,8	8,8	8,8	11,9	11,9	17,8	18,0
Rozměry D x Š x V (mm)	226 x 178 x 206		262 x 216 x 228			294 x 226 x 247		375 x 231 x 219	
Připojovací potrubí (Ø mm)	18		18			18		26	